

MarineBoost^{5.1}



- Model number: SD-RP1001LGDWH-O
- Frequency(Mhz): GSM(900/1800) + 3G(2100) + 4G(800/1800/2600)
- Networks:

Frequency bands(Mhz):	(791_862) + (880_960) + (1710_1880) + (1920_2170) + (2500_2690)	
Coverage:	3-5 (rooms)	
Number of People:	unlimited	
Gain:	Uplink Gp > 50dB	Downlink Gp > 60dB
Pass band ripple:	< 4dB	
I/O impedance:	50 ohm/N connector	
Max uplink/downlink signal strength:	17dBm / 3dBm	
Ambient Temperature:	-30°C to +70°C	
Power supply input:	110 - 240V AC	
Power supply output:	12v DC	
Oscillation Control	Automatic	
Level Control:	Automatic*	
Uplink Switch Off	Yes**	
AGC Range	30db	
Surge protection	SMA connectors DC grounded, 12V DC port MOV protected	

Antenna Specifications

Indoor antenna

outdoor omni antenna

Nominal Gain	6.4dBi / 9.4dBi	4.5dBi / 5dBi
3dB beam Pattern	60° x 60°	38° / 35° omni
Bandwidth	790-960MHz + 1710-2700MHz	790-960MHz + 1710-2700MHz
VSWR	<1.4	<2
Front to Back Ratio	> 20dB	> 20dB
Polarization	Vertical	Vertical
Power Rating	50W	100W
Impedance	50-OHM	50-OHM
Termination	SMA male	N-Female
Cross Pol. Discrimination	-20dB	-20dB
Dimensions	210 x 180 x 43mm	365 x 33mm
Weight	0.68kg	0.39kg
Rated wind velocity	126km/hr	216Km/h
Working temperature	-40°C to +65°C	-40°C to +65°C

Power Supply Specification

AC	100-240V	50-60Hz
DC input	12V	2.6A
Typical power usage	30W	

Mechanical Specification

Length	35cm
Width	30cm
Depth	4.3cm
Weight	2kg
Mounting	4 x 5mm holes for mounting

* Automatically adjusts during installation. Thereafter, automatically adjusts for seasonal variation in pathloss between Basestation and Outdoor Antenna.

** The uplink amplifiers switch off when the repeater is not in use, thus reducing the uplink noise to almost zero. When the repeater is in use (eg phone call being made), the uplink amplifier switches on for the duration of the call and a blue LED switches on indicating this is the case.

Note: Specifications subject to change without notice.